

DOWNLIGHT COMFORT

INDIRECT LIGHT



	A mm	B mm	mm	g
8 W	Ø107	31	Ø95-100	159
16 W	Ø172	50	Ø155-160	312
24 W	Ø225	60	Ø210-215	374

	SOURCE	OUTPUT				
8 W	1.030 lm	400 lm	220-240 V/AC	3000K	CMF-081130	21,50 €
				4000K	CMF-081140	
16 W	2.090 lm	880 lm	85-265 V/AC	3000K	CMF-161830	38,00 €
				4000K	CMF-161840	
24 W	3.260 lm	1.320 lm	220-240 V/AC	3000K	CMF-242330	55,00€
				4000K	CMF-242340	



ALUMINUM DRIVER INCL.



COMPLIANCE

Apparecchio a incasso fisso LED. Illuminazione indiretta per un'ottimale ed omogenea distribuzione della luce.

Fixed recessed LED downlight. Indirect lighting for optimal and uniform light distribution.

EMC DIRECTIVE 2014/30/EU | EN 55015:2013 /A1:2015 | EN 61547:2009 | EN 61000 3-2:2014 | EN 61000 3-3:2013
LVD DIRECTIVE 2014/35/EU | EN 60598-1:2015+A1:2018 | EN 60598 2-2:2012 | EN 62471:2008 | EN 62493:2015
ROHS DIRECTIVE 2011/65/CE | IEC62311-5:2013 | IEC62321-7-1:2015 | IEC62321-7-2:2017 | IEC623 21-4:2017 | IEC62321-6:2015 | IEC 62321-8:2017