

TUBI LED
FULL VISION +

160
lm/W

HIGH EFFICIENCY



FULL VISION + 160 lm/W

	A mm	g
9 W	600	96
18 W	1200	176
22 W	1500	210

G13	W	lm	OUTPUT		Pcs	€
			K	Model		
	9 W	1.440	4000 K	FVT8M160-096040	25	6,00
			6500 K	FVT8M160-096065		
	18 W	2.880	4000 K	FVT8M160-181240	25	8,50
			6500 K	FVT8M160-181265		
	22 W	3.520	4000 K	FVT8M160-221540	25	9,90
			6500 K	FVT8M160-221565		

220-240 V IP20 270°

OPAL GLASS 160 lm/W

WIRING DIAGRAMS



WIRING DIAGRAMS



RELAMPING

Spegnere la Rete.
Turn off the mains.

Rimuovere tutti i tubi fluorescenti esistenti.
Remove all fluorescent tubes.

Rimuovere gli starter e installare quello in dotazione.
Remove the starter and install the supplied one.

Installare FULL VISION +
Install FULL VISION +

Ripristinare la Rete
Turn on the mains.

Tubo LED idoneo per plafoniere con parabola riflettente. Struttura in vetro opale per un fascio luminoso omogeneo. Alta Efficienza 160 lm/W.

LED tube suitable for ceiling lights with reflector. Opal glass structure for a homogeneous light beam. 160 lm/W high efficiency.

INDUSTRIAL PACK



DISTRIBUITI IN CONFEZIONE INDUSTRIALE DA 25 PZ CON FOAM PROTETTIVO
DISTRIBUTED IN 25 PCS INDUSTRIAL PACK WITH PROTECTIVE FOAM