

NEW
PLAFONIERA LINEARE
SPEEDY

TRICOLOR
3000K
4000K
6500K

EASY



| | A mm | g | Max |
|------|---------|-----|-------|
| 4 W | 313 | 68 | 25 pz |
| 8 W | 573 | 106 | 12 pz |
| 10 W | 873 | 142 | 10 pz |
| 14 W | 1173 | 186 | 7 pz |
| 18 W | 1478 | 355 | 5 pz |

| OUTPUT | | | | | |
|--------|----------|--------------------------|-----------------------|------|---------|
| 4 W | 400 lm | 3000 K - 4000 K - 6500 K | SPD-043000 | 6/24 | 13,75 € |
| 8 W | 800 lm | 3000 K - 4000 K - 6500 K | SPD-086000 | 6/24 | 18,00 € |
| 10 W | 1.000 lm | 3000 K - 4000 K - 6500 K | SPD-109000 NEW | 6/24 | 23,50 € |
| 14 W | 1.400 lm | 3000 K - 4000 K - 6500 K | SPD-141200 NEW | 6/24 | 27,25 € |
| 18 W | 1.850 lm | 3000 K - 4000 K - 6500 K | SPD-181500 | 6/24 | 36,25 € |

200-240 V IP20 120°

CONNECTABLE EASY TO INSTALL CCT TRICOLOR

OPTIONAL

CAVETTO DI RACCORDO FLESSIBILE
FLEXIBLE CONNECTION CABLE

| | | |
|---------------|-------|--------|
| RC-SPD | 6/100 | 3,00 € |
|---------------|-------|--------|

INCLUDED

CAVO DA 1,5 METRI CON SPINA
1.5 METER CABLE WITH PLUG

CLIP DI FISSAGGIO
FIXING CLIPS

TECHNICAL NOTES



REGOLAZIONE DEL COLORE LUCE TRAMITE SELETTORE
COLOR TEMPERATURE ADJUSTMENT THROUGH SWITCH

Plafoniera innestabile l'una nell'altra
a filo continuo. Luce funzionale di alta qualità.

Linkable ceiling light.
Functional high quality fixture.